

LTR 6170 TWIN



LAMTRAC



Note: The specifications are given under ideal conditions and on the basis of adequate operator skill and ability.

Features

Cummins QSB 4.5 Tier III
Single Boom Arm
86% Peripheral Visibility
Side Door Entry
Double Escape Hatch (Ingress & Egress)

Dimensions

Track Width	450 mm	17.75"
Overall Length	3886 mm	153"
Overall Width	1848 mm	72.75"
Overall Height	2210 mm	87"
Ground Clearance	406 mm	16"
Ground Pressure (no attachment)	31.16 kPa	4.52 psi
Weight	6400 kg	14,110 lbs

Performance

Speed		
Variable Speed Range	0-12.5 km/h	0-7.8 mph
Hydraulic Flow	44 GPM	6000 PSI

Engine

Make	Cummins
Model	QSB 4.5
Displacement	4.5 L
Horsepower	165 hp (125 kW) @ 2000 RPM
Torque	460 ft·lbf (624 N·m) @ 1500 RPM

Tracks

Rubber Compound Track

Capacities

Fuel Tank	170 Liters	45 gallons
Hydraulic Tank	89.3 Liters	23.6 gallons

Electrical

Voltage		12 Volts
Battery Capacity	1500 CCA	310 RC@25 A
Alternator		160 A

Standard Equipment

Air ride seat with fully adjustable controls
Air Conditioning
Digital Dash Display
Convenience 12 V Power Port
Ingress & Egress Roof Escape
Dome Light
Joystick Controls
HVAC System
Certified Cab - ROPS / FOPS / OPS
Superior Capacity Cooling
High Definition Rear View Camera
Hydraulic Winch (15,000 lbs)



Optional Equipment

Mulching Head	Bucket, General Purpose	Power Box Rake
Root Rake	Bucket, Light Material	Snow Blade
Auger	Bucket, Multi-Purpose	Snow Blower
Backhoe	Brush Cutter, Rotary	Stump Grinder
Broom, Rotary	Dozer Blade	Trencher
Pallet Forks	Land Leveler	Vibratory Roller
Dozer Rake	Rotary Cutter	

250 Exportation Street

Tracadie-Sheila, NB

Canada

E1X 1A2

Tel. 1.888.LAMTRAC

Fax. 506.393.8501

www.lamtrac.com