

D 90_{SW}




All pictures shown are for illustrative purposes only and may contain optional equipment.

DUMPER SYSTEM

Featuring a 4x4x4 hydrostatic transmission (i.e. four-wheel drive and four-wheel steering for a smaller turning radius), the FIORI SW-series dumpers are equipped with a 180° positioning tipping body for unloading on three sides, which ensures maximum coverage of the construction site. With a 9,000 kg load capacity, the D 90 SW model is the most suitable dumper for conventional applications where manoeuvrability, visibility, and comfort (low cab, oscillating front axle with tilt-limiting system) are essential requirements. The operator protection guaranteed by the standard Level II ROPS/FOPS cab and the unrivalled visibility allowed by the exclusive driving reversibility system, guarantee the operator the utmost safety when driving the D 90 SW in either direction.

FIORI



DIESEL ENGINE	No emission compliance	Stage IIIA / Tier 3	Tier 4 Final EPA	Stage V
Model :	PERKINS serie 1104	PERKINS serie 1104	KOHLER serie KDI 2504	KOHLER serie KDI 2504
Type :	Aspirated	Turbo	Turbo Intercooler	Turbo Intercooler
Total displacement :	4400cc - 4 in linea	4400cc - 4 in line	2482cc - 4 in line	2482cc - 4 in line
Injection :	Mechanical control with direct injection	Mechanical control with direct injection	Electronic control with Common Rail	Electronic control with Common Rail
Aftertreatment sys. :	-	-	EGR + DOC	EGR + DOC + DPF
Cooling :	air water, dry air filter	air water, dry air filter	air water, dry air filter	air water, dry air filter
Maximum power :	64.5 kW (87 Hp)	74 kW (101 Hp)	55,4 kW (74,3 Hp)	55,4 kW (74,3 Hp)
Adj. power. :	64 kW (2400 rpm)	70 kW (2200 rpm)	55,4 kW (2300 rpm)	55,4 kW (2300 rpm)
Maximum torque :	293 Nm a 1400 rpm	392 Nm a 1400 rpm	300 Nm a 1500 rpm	300 Nm a 1500 rpm
Alternator :	12V - 65 A	12V - 65 A	12V - 80 A	12V - 90 A

ELECTRIC SYSTEM

Battery: 12 V - 132 Ah (600 A)
Road light system, rear working lights.

4X4 FOUR-WHEEL DRIVE

Hydrostatic "automotive" transmission with variable displacement pump and variable displacement hydraulic motor with electro-hydraulic control, and reverse gear control on the steering wheel.
Electro-hydraulically controlled mechanical gearbox for "working speed" and "road transfer" speed.

SPEED

4 forward gears 2 reverse gears
Ist 0 - 3.0 Km/h 0 - 3.0 Km/h
IInd 0 - 7.2 Km/h 0 - 3.0 Km/h
IIIRD 0 - 10.0 Km/h 0 - 10.0 Km/h
IVth 0 - 25.0 Km/h 0 - 10.0 Km/h
Traction / weight ratio 48%

AXLES AND WHEELS

Front load-bearing, oscillating ($\pm 6^\circ$) and steering with planetary reduction gears on the wheel hubs.
Rear load-bearing and steering with planetary reduction gears on the wheel hubs and directly flanged gearbox.
Tyres 405/70-20 16PR

BRAKES

Internal oil-bath disc service and emergency brakes acting on the 4 wheels, activation with miniservo pump on independent dual circuit.
Negative type parking brake, with internal oil-bath discs on the rear axle and electro-hydraulically controlled release.

STEERING

Assisted by means of load-sensing power steering with double displacement on 4 steering wheels; steering selection device for: 2 steering wheels, 4 steering wheels - crab steering.

EQUIPMENT HYDRAULIC SYSTEM

Gear pump
Max. flow rate: 45 litres/min.
Maximum pressure: 230 bar
2 - elements distributor.
Aluminium heat exchanger for hydraulic oil cooling.
Pressurised closed-circuit intake with oil filter replaceable from the outside.

DUMP BODY

Dump body with tilting by means of 2 double-acting jacks. Orientation over 180° for trilateral unloading by means of "heavy-duty" ball fifth wheel, with hydraulic rotation and automatic locking by means of negative brake.
Struck capacity 3500 litres
SAE heaped capacity 4800 litres

CAB

Closed cab with heating system, designed in accordance with ROPS FOPS.
 180° pivoting driving post. Anatomic seat with flexible suspension and height adjustment, seat belts.
Driving and equipment controls with ergonomic arrangement.
Sliding window on cabin door.
LCD TV display with camera for rear visibility.

SERVICE REFILL CAPACITIES

Fuel tank in cross-linked polyethylene, 95 litres
Total hydraulic system capacity: 105 litres
Engine oil: 8 kg

WEIGHTS

Operating weight 5600 kg
Max gross weight: 14800 kg
load-carrying capacity: 9000 kg