



K-TEC 1237 ADT

The K-Tec 1237ADT is a ruggedly versatile earthmover, making it K-Tec's most popular ADT scraper favored for equipment fleets. The modular 1237ADT scraper's bolt-together design allows for an affordable international container shipment, as well as simple maintenance. This fast, strong, multi-purpose machine; carrying a heaped capacity of 37 cubic yards / 28.3 cubic metres, is a powerful worker in any soil condition or job site application.



K-TEC 1237 ADT SCRAPER FEATURES

LUBE TEC	TENSILE TEC	LOAD TEC	CUSHION RIDE	SELF LOAD	TOP LOAD
PUSH LOAD	ADAPTABLE	WARRANTY	SHIPPING	CERTIFIED	CERTIFIED

1237 ADT SPECIFICATIONS

General Specifications	Standard	Metric
Heaped Capacity (ISO)	37 Cubic Yards	28.28 Cubic Metres
Struck Capacity	20.25 Cubic Yards	15.5 Cubic Metres
Max Loading Rating	88,000 lbs	39,916 kgs
Bucket Dimensions	12' W x 4' 3" H x 12' 10" L	3.66m W x 1.29m H x 3.91m L
Cutting Width	12'	3.66m
Cutting Edge	3-Piece Blade	3-Piece Blade
Gate Opening	6' 8"	2.03m
Turning Radius	30'	9.1m
Gate Cylinders	5" x 26"	127mm x 711mm
Lift Cylinders	5.5" x 32"	140mm x 813mm
Ejector Cylinder	5.5" x 76"	140mm x 1,930mm
Cutting Edge Clearance	28"	0.71m
Ball to Rear Axle Length	28' 9"	8.77m
Rack Height (Tilttable)	4'	1.22m
Weight Distribution	30% Hitch, 70% Scraper Axle	30% Hitch, 70% Scraper Axle
4 Tires	26.5 R25 Radial	26.5 R25 Radial
Horsepower Required	400HP +	294 kW +
Wrap Around Mud Scrapers	Standard	Standard
Gate Extension	Standard	Standard
Truck Fender & Catwalk System	Standard	Standard
Transport Dimensions	Standard	Metric
Overall Width	14'	4.27m
Overall Height	10'	3.04
Overall Length	36' 6"	11.13m
Shipping Weight	39,130 lbs	17,749 kgs
Overseas Shipping	40' Highcube container	40' Highcube container
Optional Upgrades		
Radial Tires (4)	1000/50 R25, 1050/50 R32 (2)	
Brake System	4 or 8 Caliper Disc System	
Skid Shoe System	Provides superior stabilization for precision finish cut	
Height Gauge	Increases cutting depth visibility	
Mine Version	Heavier plate steel for mining applications	

Specifications are subject to change without notice.



Sand • Texas, USA



Clay • Japan




Topsoil • Iowa, USA



Topsoil • Australia

RECOMMENDED POWER UNIT



400HP +/298 KW +
Articulated Dump Truck