

Technical sheet :


# **MTA 5519 S3**

---




Capacities		Imperial
Max. capacity		5501 lb
Max. lifting height		19 ft
Max. outreach		11 ft
Weight and dimensions		
Overall length to carriage	l11	12 ft 4 in
Overall length (with forks)	l1	12 ft 4 in
Overall width	b1	5 ft 11 in
Overall height	h17	6 ft 4 in
Wheelbase	y	7 ft 6 in
Ground clearance	m4	10 in
Overall cab width	b4	28 in
Tilt-up angle	a4	12 °
Tilt-down angle	a5	100 °
External turning radius	Wa3	11 ft
Unladen weight (with forks)		9700 lb
Standard tyres		12 x 16.5
Performances		
Lifting		8 s
Lowering		5 s
Extension		7 s
Retraction		6 s
Crowd		4 s
Dump		4 s
Engine		
Engine brand		Yanmar
Engine norm		Tier 4 final
Engine model		4TNV98
Number of cylinders / Capacity of cylinders		4 - 0 in³
Power (kW)		50.70 kW
Max. torque / Engine rotation		235 Nm @ 235 rpm
Transmission		
Transmission type		Hydrostatic
Number of gears (forward / reverse)		2 / 2
Parking brake		SAHR
Service brake		Wet disc brakes
Axle Manufacturer		Dana
Hydraulics		
Hydraulic pump type		Gear pump
Hydraulic flow / Pressure		83 l/min / 3350 PSI
Tank capacities		
Engine oil		2 US gal
Hydraulic oil		18 US gal
Fuel tank		17 US gal
Miscellaneous		
Steering wheels (front / rear)		2 / 2
Drive wheels (front / rear)		2 / 2
Safety cab homologation		ROPS/FOPS
Controls		Single Joystick FNR

# MTA 5519 S3 - Dimensional drawing



# MTA 5519 S3 - Load chart

Load Chart imperial



183488



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes