## **R4**

Date of printing 10/18/2023

## Technical data

NOTE: The photo shows a general example of the product.

Machine weight, max	22045 - 35275 lb	
Max bucket width	63 in	
Max breakout force	28100 lbf	
Max breakout torque	120225 ft.lb	
Weight (from)	838 lb	
Tilt angle (2x)	40°	
Rotation speed (1 rotation per)	7.0 s at 16 gpm	
Working pressure	3626 psi	
Max return line pressure	290 psi at 25 gpm	
Min hydraulic flow	24.04 gpm	
Number of lubrication points	6	
Turning torque	5635 ft.lb at 3626 psi	
Tilt torque singe-acting cylinders	19545 ft.lb	
Tilt torque double acting cylinders	28470 ft.lb	



## **Dimensions**

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
28,7 in	40,83 in	27,76 in	19,8 in

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.



